











About the product

Marble adhesive coating with earthy tones, designed for walls and furniture to create warm interiors with a bold mineral expression.



Characteristics

 SUPPORT Vinyle	 ADHESIF Acrylique Polymère
 PROTECTEUR PET siliconé	 EPAISSEUR AVEC LINER 366 microns
 EPAISSEUR SANS LINER 212 microns	 EPAISSEUR LINER 154 microns
 FACE D'APPLICATION Intérieure	 RESISTANCE Optimale
 T° D'APPLICATION min 5°C	NORMES EUROCLASSES

Available sizes

WIDTH 1.22 M





5 m

10 m

30 m

50 m

Features

-  **Durability**
12 to 15 years in Central Europe
-  **Usage**
Designed for all types of glazing
-  **Maintenance**
After 30 days, non-abrasive solution
-  **Storage**
2 years, away from moisture

Application guide

Application method

The surface to be bonded must be free of dust, grease or any other contaminant. Some materials such as polycarbonate may cause bubbling problems. A compatibility test is therefore recommended.

Production tracking

In order to continuously improve our production, we may modify the colors and manufacturing processes of our products without notice. We recommend ensuring that they are exactly suitable for the intended use.

Certifications

Product compliant with European standards EN 13501 (fire reaction) and Euroclass for fire safety. Certified for indoor use.

🕒 23/05/2026 00:50