

### About the product

Light silver adhesive coating with a luminous expression, designed for walls and furniture to bring clarity and lightness to contemporary interiors.



### Characteristics

|   |  |
|---|--|
|  <b>SUPPORT</b><br>Vinyle                     |  <b>ADHESIF</b><br>Acrylique<br>Polymère      |
|  <b>PROTECTEUR</b><br>PET siliconé          |  <b>EPAISSEUR AVEC LINER</b><br>373 microns |
|  <b>EPAISSEUR SANS LINER</b><br>226 microns |  <b>EPAISSEUR LINER</b><br>147 microns      |
|  <b>FACE D'APPLICATION</b><br>Intérieure    |  <b>RESISTANCE</b><br>Optimale              |
|  <b>T° D'APPLICATION</b><br>min 5°C         | <b>NORMES</b><br>EUROCLASSES   |

### Available sizes

WIDTH 1.22 M





5 m

10 m

30 m

50 m

### Features

-  **Durability**  
12 to 15 years in Central Europe
-  **Usage**  
Designed for all types of glazing
-  **Maintenance**  
After 30 days, non-abrasive solution
-  **Storage**  
2 years, away from moisture

### Application guide

#### Application method

The surface to be bonded must be free of dust, grease or any other contaminant. Some materials such as polycarbonate may cause bubbling problems. A compatibility test is therefore recommended.

#### Production tracking

In order to continuously improve our production, we may modify the colors and manufacturing processes of our products without notice. We recommend ensuring that they are exactly suitable for the intended use.

#### Certifications

Product compliant with European standards EN 13501 (fire reaction) and Euroclass for fire safety. Certified for indoor use.

🕒 23/05/2026 00:49