


About the product

Metal adhesive coating with a raw look, designed for walls and furniture to assert a bold, industrial interior style.



Characteristics

-  **SUPPORT**
Vinyle
-  **ADHESIF**
Acrylique
Polymère
-  **PROTECTEUR**
PET siliconé
-  **EPAISSEUR AVEC LINER**
350 microns
-  **EPAISSEUR SANS LINER**
214 microns
-  **EPAISSEUR LINER**
136 microns
-  **FACE D'APPLICATION**
Intérieure
-  **RESISTANCE**
Optimale
-  **T° D'APPLICATION**
min 5°C
- NORMES EUROCLASSES**

Available sizes

WIDTH 1.22 M

- 5 m
- 10 m
- 30 m
- 50 m

Features

-  **Durability**
12 to 15 years in Central Europe
-  **Usage**
Designed for all types of glazing
-  **Maintenance**
After 30 days, non-abrasive solution
-  **Storage**
2 years, away from moisture

Application guide

Application method

The surface to be bonded must be free of dust, grease or any other contaminant. Some materials such as polycarbonate may cause bubbling problems. A compatibility test is therefore recommended.

Production tracking

In order to continuously improve our production, we may modify the colors and manufacturing processes of our products without notice. We recommend ensuring that they are exactly suitable for the intended use.

Certifications

Product compliant with European standards EN 13501 (fire reaction) and Euroclass for fire safety. Certified for indoor use.

🕒 23/05/2026 00:54